



Type 7010



pneumatic actuated stopvalve, 2-2-way – stainless steel

single acting (SA), for high switching frequency and flow capacities

Butt weld ends in accordance with DIN

Connection: actuator $\varnothing$ 50 – G $\frac{1}{8}$ “; piston $\varnothing$ 80 / $\varnothing$ 125 – G $\frac{1}{4}$ “

High-temperature-design, head-unit gasket: KLINGER®top-chem2000

Cone and pistonrod calking!

N. diameter:	DN15 ... DN40
N. pressure:	PN40
Body:	stainless steel 1.4408
Actuator:	stainless steel
Seat / Gasket:	PTFE; PEEK / head unitgasket KLINGER®top-chem2000
Temperature:	PTFE up to 200 °C; PEEK up to 220 °C
Face-to-face:	in accordance with DIN 3202, T4 M8
Optional (Extract):	replacement actuator, repair-set

N. diameter DN	Actuator		Seat	Controller ¹	KST ²	STA ³	Order code	
	Size	Spring						
15	K $\varnothing$ 50	1	PTFE	0	ja	-	SS-7010-81160	
							SS-7010-81161	Act. Replacement
							SS-7010-80732	Repair-set
15	K $\varnothing$ 50	2	PTFE	2	ja	-	SS-7010-81742	
							SS-7010-82485	Act. Replacement
							SS-7010-80732	Repair-set
15	K $\varnothing$ 50	2	PEEK	2	-	-	SS-7010-59827	
							SS-7010-81275	Act. Replacement
							SS-7010-81224	Repair-set
25	K $\varnothing$ 50	2	PTFE	2	-	-	SS-7010-81741	
							SS-7010-84440	Act. Replacement
							SS-7010-51559	Repair-set
25	K $\varnothing$ 50	2	PTFE	0	ja	-	SS-7010-82473	
							SS-7010-82484	Act. Replacement
							SS-7010-02505	Repair-set
25	K $\varnothing$ 80	1	PEEK	1	-	ja	SS-7010-80481	
							SS-7010-82151	Act. Replacement
							SS-7010-80482	Repair-set
25	K $\varnothing$ 80	2	PEEK	2	-	-	SS-7010-59833	
							SS-7010-81162	Act. Replacement
							SS-7010-82039	Repair-set
32	K $\varnothing$ 50	2	PTFE	0	ja	-	SS-7010-81739	
							SS-7010-81163	Act. Replacement
							SS-7010-52749	Repair-set
32	K $\varnothing$ 50	2	PEEK	0	-	-	SS-7010-81228	
							SS-7010-84441	Act. Replacement
							SS-7010-81226	Repair-set
32	K $\varnothing$ 80	1	PEEK	1	-	ja	SS-7010-59834	
							SS-7010-82951	Act. Replacement
							SS-7010-81215	Repair-set
32	K $\varnothing$ 125	3	PEEK	2	-	-	SS-7010-59830	
							SS-7010-81276	Act. Replacement
							SS-7010-80872	Repair-set
40	K $\varnothing$ 50	2	PTFE	0	ja	-	SS-7010-81740	
							SS-7010-81277	Act. Replacement
							SS-7010-58757	Repair-set
40	K $\varnothing$ 80	1	PEEK	1	-	ja	SS-7010-81738	
							SS-7010-84442	Act. Replacement
							SS-7010-81412	Repair-set
40	K $\varnothing$ 125	2	PEEK	1	-*	ja	SS-7010-80479	
							SS-7010-83186	Act. Replacement
							SS-7010-82685	Repair-set

¹ Controller: 0 Spring closed (NC closing with the flow), 1 Spring opened (NC closing against flow), 2 Spring closed (NC closing against flow)

² KST = Head-unit extension

³ STA = Position indicator pin

*with reinforced head unit