



Type CK3M



Check valve with threaded socket connection – stainless steel

metallic sealing, compact, for steam applications, any mounting position / employment
Female thread in accordance with DIN ISO 228-1; on request ASME / ANSI B1.20.1 (NPT)

Order code

Type CK3M	RSV-CK3M-15D
-----------	--------------

N. diameter: DN15, 1/2"
N. pressure: PN21, min. opening- / differential pressure 0,02 bar
Body: stainless steel 1.4308 (A351 Gr.CF8)
Spring: stainless steel 1.4301 (AISI 304)
Gasket: metallic sealing
Temperature: 220 °C at steam applications
Face-to-face: 55 mm

INSPECTION GLASSSES



Type T5N



Compact-inspection glass – grey cast iron

with flow indication (ball PTFE) for low to large flow capacities
Female thread in accordance with DIN ISO 228-1; on request ASME / ANSI B1.20.1 (NPT)

Order code

Type T5N	SG-T5N-15D
----------	------------

N. diameter: DN15, 1/2"
N. pressure: PN10 max. permitted operating pressure
Body: grey cast iron EN-GJL-250 (EN-JL-1040), ASTM A126 Cl.B, old: GG-25
Inspection glass: heat resistant glass
Gasket: EPDM
Temperature: up to 120 °C
Face-to-face: 68 mm
Weight: 1,1 kg